

SPECIFICATIONS

Gator Guard Environmental Products Inc. Reusable Sediment Control Wattle

Model No.	RSW625
Diameter	6-inch
Length	25-feet
Apron Width	8-inch
Connection Sleeve	12-inch (at one end)
Weight – Single Roll	8-pounds
- Three Pack	25-pounds
Dimensions – Single Roll	38-in diameter x 7-in thick
- Three Pack	38-in diameter x 21-in thick
Fabric: - Material	Woven polypropylene slit film
- Type	Ground Cover
- Weight	3.2 oz./sq. yd.
- Tensile Strength	175 x 110 lbs.
- Burst	275 psi
- Puncture	65 lbs.
- Water Permeability	15-gpm/sf clean water <1-gpm/sf dirty water
- UV % Strength	80% after 2400 hrs.
Thread	UV Resistant Polyester
Foam Filler (recycled scrap)	Closed cell polyethylene foam
Install Pins 4-in, 5-in, 6-in Cap Nails	14 included (in center of roll)
Alt. Install Pins 6-inch Landscape Staples	14 included (in center of roll) alternate
Alt. Install Pins - Big Nails with Washers	Purchase Locally
Installation Pin Spacing	Every 3-feet
11-inch Cable Ties (for cut-to-length)	2 included (in apron below tag)
Cover apron w/ dirt (compact w/ feet)	1-inch of dirt minimum
Accidental cut repair	Fill cut with caulking or replace
Functional Life (expected)	5 years (excludes major damage)
Soils Lab Testing	San Diego State University – Jan. 2008
% Effective LA Basin 10-yr storm Equiv.	98% effective for 3:1 slope

Date: Sept 18, 2008 – The above properties are typical averages.
All test methods are ASTM or Industry Standards.